

**Create the future  
NXTR-A**

**Specifications** NXTR A model

Module			1R module			2R module		
Panel size (L x W)	Single conveyor		48 x 48 to 750 x 610 mm			48 x 48 to 370 x 610 mm		
	Double conveyor	Single conveyance	48 x 48 to 750 x 510 mm			48 x 48 to 370 x 510 mm		
		Dual conveyance	48 x 48 to 750 x 280 mm			48 x 48 to 370 x 280 mm		
Weight	Double conveyor		610 kg			730 kg		
Base			One module base			Two module base		
Air consumption			70 L/min (ANR)			140 L/min (ANR)		
Weight <sup>*1</sup>			480 kg			910 kg		
Head			RH28	RH20	RH08	RH02	RH01	
Throughput <sup>*2</sup>			55,000 cph	50,000 cph	30,000 cph	9,000 cph	6,000 cph	
	Productivity priority mode		60,000 cph	55,000 cph	-	-	-	
Placing accuracy <sup>*2</sup>			±0.025 mm Cpk ≥ 1.00					
	Heightened accuracy mode <sup>*3</sup>		±0.015 mm 3σ	-	-	-	-	
Power			3-phase AC 200 to 230 V ±10 V (50/60 Hz)					
Air			0.4 MPa					

<sup>\*1</sup> The two module base dedicated for 1R modules is 890 kg.  
<sup>\*2</sup> Under optimum Fuji conditions.  
<sup>\*3</sup> This mode applies to 2R modules.

The content is subject to change without notice due to constant product development.  
 The information is current as of July 2024.  
 ©2024 FUJI CORPORATION. All Rights Reserved.