

**Create the future
NXTR PM**

■ Specifications

			NXTR PM	NXTR PM with PM Smart Changer ^{*1,2}
Repeated alignment accuracy ^{*3}			±0.010 mm Cpk ≥ 2.0 (6σ)	
Printing accuracy ^{*3}			±0.020 mm Cpk ≥ 2.0 (6σ)	
Squeegee speed			1 to 300 mm/sec	
Panel size (L x W)	Single conveyor		48 x 48 mm to 610 x 610 mm	
	Double conveyor	Single conveyance	48 x 48 mm to 610 x 510 mm	
		Dual conveyance	48 x 48 mm to 330 x 280 mm	
Metal stencil frame size (L x W)			650 x 550 mm, 29 x 29 inch, 750 x 750 mm, 750 x 810 mm	
Backup block size			380 mm, 480 mm, 560 mm, 620 mm	48 x 38 mm to 330 x 270 mm
PM Smart Changer rack levels			-	4 levels
Weight			1,600 kg	1,800 kg
Power			3-phase AC 200 to 230 V ±10 V (50/60 Hz)	
Air			0.4 MPa	
Air consumption			37 L/min (ANR)	

*1 Option

*2 Conditions apply for automatically exchanging metal stencils and backup blocks.

*3 Under optimum Fujii conditions.

The content is subject to change without notice due to constant product development.

The information is current as of July 2024.

©2024 FUJII CORPORATION. All Rights Reserved.