

**Create the future
NXTR A**

Specifications NXTR A model

Module		1R module			2R module		
Panel size (L x W)	Single conveyor	48 x 48 to 750 x 610 mm			48 x 48 to 370 x 610 mm		
	Double conveyor	Single conveyance	48 x 48 to 750 x 510 mm			48 x 48 to 370 x 510 mm	
		Dual conveyance	48 x 48 to 750 x 280 mm			48 x 48 to 370 x 280 mm	
Weight	Double conveyor	610 kg			730 kg		
Base		One module base			Two module base		
Air consumption		70 L/min (ANR)			140 L/min (ANR)		
Weight ¹		480 kg			910 kg		
Head		RH28	RH20	RH08	RH02	RH01	
Throughput ²		55,000 cph	50,000 cph	30,000 cph	9,000 cph	6,000 cph	
	Productivity priority mode	60,000 cph	55,000 cph	-	-	-	
Placing accuracy ²		±0.025 mm Cpk ≥ 1.00					
	Heightened accuracy mode ³	±0.015 mm 3σ	±0.010 mm 3σ		-	-	
Power		3-phase AC 200 to 230 V ±10 V (50/60 Hz)					
Air		0.4 MPa					

¹ The two module base dedicated for 1R modules is 890 kg.
² Under optimum Fuji conditions.
³ This mode applies to 2R modules.

The content is subject to change without notice due to constant product development.
 The information is current as of January 2025.
 ©2025 FUJI CORPORATION. All Rights Reserved.